



SAFETY DATA SHEET

ETHYL ACETATE

Page 1

Issued:

Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: ETHYL ACETATE
CAS number: 141-78-6
EINECS number: 205-500-4
Index number: 607-022-00-5
Product code: E-TAC
Synonyms: ETHYL ESTER
ETHYL ETHANOATE
VINEGAR NAPHTHA
ETAC
Company name: BULK RESOURCES LIMITED
Ventureforth House
South Denes Rd
Great Yarmouth
Norfolk
NR30 3PT
United Kingdom
Tel: 0044 (0) 1493 660800
Fax: 0044 (0) 1493 331295
Emergency tel: 0044 (0) 1493 660800
Email: sales@bulkresources.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking.
Vapours may cause drowsiness and dizziness.
Other hazards: In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ETHYL ACETATE 100.000%

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness. The eyes may water profusely.
Ingestion: There may be soreness and redness of the mouth and throat.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

[cont...]

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure limits

WEL (8 hr TWA): 200 ppm

WEL (15 min STEL): 400 ppm

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Gloves (solvent-resistant).

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Solubility in water: Miscible

Boiling point/range°C: 77

Melting point/range°C: -84

Flammability limits %: lower: 2.1

upper: 11.5

Flash point°C: -4

Part.coeff. n-octanol/water: 0.60

Autoflammability°C: 460

Vapour pressure: 100mm@27°C

Relative density: 0.90

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute toxicity: ETHYL ACETATE

ORL MUS LD50 4100 mg/kg

ORL RAT LD50 5620 mg/kg

SCU RAT LDLO 5 gm/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1173 **ADR Class:** 3
Packing group: II **Classification code:** F1
Shipping name: ETHYL ACETATE
Labelling: 3 **Hazard ID no:** 33

**IMDG / IMO**

UN no: 1173 **Class:** 3
Packing group: II **EmS:** 3-07
Marine pollutant: NO
Labelling: 3

IATA / ICAO

UN no: 1173 **Class:** 3
Packing group: II
Packing instructions: 305(P&CA); 307(PAO)
Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Highly flammable.

Irritant.



Risk phrases: R11: Highly flammable.
R36: Irritating to eyes.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S16: Keep away from sources of ignition - No smoking.
S23: Do not breathe vapour.
S25: Avoid contact with eyes.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

SAFETY DATA SHEET

ETHYL ACETATE

S33: Take precautionary measures against static discharges.

S39: Wear eye / face protection.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.