



## SAFETY DATA SHEET

N-BUTYL ACETATE

Page 1

Issued:

Revision No: 1

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** N-BUTYL ACETATE  
**CAS number:** 123-86-4  
**EINECS number:** 204-658-1  
**Index number:** 607-025-00-1  
**Product code:** NBA  
**Company name:** BULK RESOURCES LIMITED  
Ventureforth House  
South Denes Rd  
Great Yarmouth  
Norfolk  
NR30 3PT  
United Kingdom  
Tel: 0044 (0) 1493 660800  
Fax: 0044 (0) 1493 331295  
Emergency tel: 0044 (0) 1493 660800  
Email: sales@bulkresources.co.uk

### 2. HAZARDS IDENTIFICATION

**Main hazards:** Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** N-BUTYL ACETATE 100.000%

### 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

### 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

## 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

**Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

## 7. HANDLING AND STORAGE

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

**Suitable packaging:** Must only be kept in original packaging.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Workplace exposure limits

**WEL (8 hr TWA):** 724 mg/m<sup>3</sup>

**WEL (15 min STEL):** 966 mg/m<sup>3</sup>

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**State:** Liquid

**Colour:** Colourless

**Odour:** Sweet-smelling

**Boiling point/range°C:** 124-128

**Flash point°C:** 25

**Autoflammability°C:** 420

**Relative density:** 0.88

**pH:** 7

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions. Stable at room temperature.

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

**Materials to avoid:** Strong oxidising agents. Strong acids.

**Haz. decomp. products:** In combustion emits toxic fumes.

## 11. TOXICOLOGICAL INFORMATION

**Acute toxicity:** N-BUTYL ACETATE

ORL MUS LD50 6 gm/kg

ORL RAT LD50 10768 mg/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

## 12. ECOLOGICAL INFORMATION

**Mobility:** Readily absorbed into soil.

**Persistence and degradability:** Biodegradable.

**Bioaccumulative potential:** No bioaccumulation potential.

**Other adverse effects:** Negligible ecotoxicity.

## 13. DISPOSAL CONSIDERATIONS

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## 14. TRANSPORT INFORMATION

### ADR / RID

**UN no:** 1123

**ADR Class:** 3

**Packing group:** II

**Classification code:** F1

**Shipping name:** BUTYL ACETATES

**Labelling:** 3

**Hazard ID no:** 33



**IMDG / IMO**

**UN no:** 1123 **Class:** 3  
**Packing group:** II **EmS:** 3-07  
**Marine pollutant:** NO  
**Labelling:** 3

**IATA / ICAO**

**UN no:** 1123 **Class:** 3  
**Packing group:** II  
**Packing instructions:** 305(P&CA); 307(PAO)  
**Labelling:** 3

**15. REGULATORY INFORMATION**

**Hazard symbols:** Irritant.



**Risk phrases:** R10: Flammable.  
R66: Repeated exposure may cause skin dryness or cracking.  
R67: Vapours may cause drowsiness and dizziness.

**Safety phrases:** S25: Avoid contact with eyes.  
S23: Do not breathe vapour.  
S36: Wear suitable protective clothing.  
S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

**16. OTHER INFORMATION**

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.